



EARTH-CHAIN MAGNETIC & PRECISION TOOLS

HORIZONTAL / VERTICAL ROTARY TABLE


MODEL:HHV



FEATURES

The Rotary Table is graduated 360 degree around its circumference and is driven by a precision Worm and Gear providing a **90:1** reduction ratio. One turn of the handle moves the Rotary Table through 4 degree.

The dial is graduated in divisions of 1 min. and the vernier scale allows readings down to 10 seconds.



25.4mm=1"

OPTIONAL ACCESSORIES

TAIL STOCK

TS-1 for HHV-200,250

TS-2 for HHV-300

TS-3 for HHV-350,400

DIVIDING PLATE SET

DP-1 for HHV-150

DP-2 for HHV-200,250

DP-3 for HHV-300,350,400

3-JAW CHUCK

FREE




Unit:mm

MODEL	Base dimension		Table		Bolt slots	Center sleeve	Worm gear Ratio	N.W.
	A	B	D	H	K			
HHV-150	220	160	150	78	15	MT-2	90:1	12.5kg
HHV-200	310	225	200	110	17	MT-3		31.0kg
HHV-250	320	280	250	110	17	MT-3		48.5kg
HHV-300	410	325	300	140	17	MT-4		77.0kg
HHV-350	460	380	350	140	17	MT-4		98.0kg
HHV-400	510	435	400	150	17	MT-5		130.0kg

TAIL STOCK (For Rotadry Table type HHV)

MODEL:TS-1, TS-2, TS-3



FEATURES

This Tail Stock can be used for accurate centering when the Rotary Table is used in the vertical position.

25.4mm=1"

Unit:mm

MODEL	Suitable for			N.W.
		Max.	Min.	
TS-1	HHV-200,HHV-250	185	122	13kg
TS-2	HHV-300	222	155	15kg
TS-3	HHV-350,HHV-400	270	208	17kg